

SUMMARY

Wires

Low	0
High	4
Coax	0
Triax	0
Quad	0
Fiber	0
Fluidic	0



Image is for illustrative purpose only

Download

[Request a quote](#)

[Catalog](#)

Series	P
Termination type	Male solder
IP rating	50
Cable Ø	4.00 - 5.20 mm
Matching parts	PLG.N0.4GL.LG
Status	
Alternative part	

TECHNICAL DETAILS

Mechanics

Shell Style/Model	PA*: Straight plug with cable collet
Keying	1 key (alpha=0; Plug: male contact; Receptacle: female contact)
Housing Material	PSU (Polysulfone), gray
Cable Fixing	∅ 4 - 5.2 mm
Variant	G : Gray collet nut for bend relief

Performance

Configuration	1P.N04 : 4 High Voltage
Insulator	
Rated Current	8 Amps

Specifications

Test voltage (kV rms) Contact-contact: 2.5
Air clearance min. (mm) or Creepage distance min. (mm): 1.30 / 3.50


Others

F ret (min): 50 N

F ret (max): 150 N
IP Rating: 50

DRAWINGS

Draws



Dimensions

	A	L
mm.	14	45
in.	0,55	1,77

RECOMMENDED BY LEMO

Tools

None

Cables