



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN AMP PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM AMP INCORPORATED, HARRISBURG, PA.

- 1 EYELETS MUST BE SEATED ON HANDLE AND TIP AS SHOWN. TIP SIDE PLAY NOT PERMISSIBLE.
- 2 SLOTTED SPRING PIN MUST BE SEATED .05 BELOW EACH END OF HANDLE.
- 3 MARKING TO BE CENTERED AND PERMANENTLY MARKED IN AREAS AS SHOWN. (COLOR OPTIONAL).
- 4. TOOL IS SPRING LOADED CLOSED, MUST OPEN AND CLOSE FREELY.
- 5 .010 MAX GAP MEASURED FROM FRONT OF TIP, WITHIN .032 LENGTH.
- 6 MEASURED WITH $\phi .154$ PIN INSERTED INTO .63 TIP LENGTH.

2	A	21920-7	*PIN, DOWEL	6
2	A	126217-1	SPRING	5
1	B	445146-1	HANDLE, LEFT SIDE	4
1	B	445145-1	HANDLE, RIGHT SIDE	3
4	B	1-26024-4	EYELET	2
2	B	445144-1	EXTRACTION TIP, HALF	1

-1	DWG SIZE	PART NO	DESCRIPTION	ITEM NO
REVISION OF EACH ASSY NO (WHEN BLANK, USE DWG REVISION)				

QTY REQD PER ASSY		PARTS LIST		
DIMENSIONS IN INCHES. TOLERANCES UNLESS OTHERWISE SPECIFIED:		MATERIAL	HEAT TREAT	FINISH
2 PLC DEC $\pm .01$		DR 12-23-87 APP 1-5-88		
3 PLC DEC $\pm .005$		M. RITRIVATO	A. J. FLAYNIK	AMP AMP INCORPORATED
4 PLC DEC \pm		CHK 1-5-88	REL -	Harrisburg, Pa. 17105
ANGLES \pm		A. J. FLAYNIK		
SURF TEXTURE: <input checked="" type="checkbox"/>		NAME TOOL, EXTRACTION		
REMOVE BURRS, BREAK SHARP EDGES .015R MAX		SCALE 2:1	DWG NO C 445147	SHEET 1 of 1 REV C

P	F	LTR	REVISION RECORD	APP	DATE	P	F	LTR	REVISION RECORD	APP	DATE

PROD	5069
CODE	DF
LOC	DF
DIST	UO