S1D13717



S1D13717 QVGA LCD Controller

The S1D13717 is a QVGA LCD Controller designed with support for digital video in embedded products. The S1D13717 contains an integrated camera interface, hardware JPEG encoder/decoder, and an SD memory card interface. Seamlessly connecting to both direct and indirect CPU interfaces, it provides support for RGB interface TFT panels. The S1D13717, with its 224 KB of embedded SRAM and rich feature set, provides a low cost, low power, single chip solution to meet the demands of embedded markets requiring digital video.


Additionally, products requiring a rotated display can take advantage of the SwivelView[™] feature which provides hardware rotation of the display memory transparent to the software application. The S1D13717 also provides support for "Picture-in-Picture" (a variable size window with overlay functions). Higher performance is provided by the hardware acceleration engine which provides 2D BitBLT functions.

The S1D13717 provides impressive support for embedded markets requiring digital video support. It's impartiality to CPU type or operating system makes it an ideal display solution for a wide variety of applications.

FEATURES

- Embedded 224 KB SRAM display buffer
- Low operating voltage
- Direct and indirect CPU interfaces
- Programmable resolutions and color depths
- Suppor for RGB interface panels
- Support for TFT panels
- Internal PLL or digital clock input
- SD memory card interface
- Single port camera interface with resize function

- Hardware JPEG encoder/decoder
- YUV to RGB converter SwivelViewTM 90°, 180°, 270° Hardware for rotation of displayed image
- Picture-in-Picture (overlay window)
- 2D hardware acceleration engine
- Software initiated power save mode
- PFBGA and QFP packages





DESCRIPTION

.

•

.

CPU Interface

Digital Video

4:2:0)

4:2:0)

Miscellaneous

Display Buffer

- 224 KB of embedded SRAM
- Addressable as a single linear address space

Panel Support

- Supports TFT panels
- 9/12/16/18-bit RGB interface
- Typical resolution of:
- up to 320x240@16bpp 0

Display Features

- 8/16 bpp support
- Picture-in-Picture: displays a variable size window overlaid over the background image
- **Overlav** functions
- Pixel doubling: doubles the effective resolution
- Video invert: inverts display data

Acceleration

- 2D BitBLT engine
- SwivelView: 90°, 180°, 270° hardware rotation of display image
- Mirror display: hardware "mirror" image of display

JAPAN

SEIKO EPSON CORPORATION

IC Sales & Marketing Department 421-8 Hino, Hino-shi, Tokvo 191-8501, JAPAN Phone: +81-42-587-5816 FAX: +81-42-587-5117

AMERICA

EPSON ELECTRONICS AMERICA, INC. 214 Devcon Drive, San Jose, CA 95112, USA

Phone: +1-800-228-3964 FAX: +1-408-922-0238

EUROPE **EPSON EUROPE ELECTRONICS GmbH**

Riesstrasse 15, 80992 Munich. GERMANY Phone: +49-89-14005-0 FAX: +49-89-14005-110

CHINA EPSON (CHINA) CO., LTD

4th Floor, Tower 1 of China Central Place, 81 Jianguo Road, Chaoyang District, Beijing 100025, CHINA

Phone: +86-10-8522-1199 FAX: +86-10-8522-1120

CHINA

SHANGHAI Branch Room 01 & 04 17F, Greenland Center II, 562 Dong An Road, Shanghai 200032, CHINA Phone: +86-21-5423-5577 FAX: +86-21-5423-4677

CHINA SHENZHEN Branch

Room 804-805 8th Floor Tower 2 Ali Center No.3331 Keyuan South RD (Shenzhen bay), Nanshan District, Shenzhen 518054, CHINA Phone: +86-10-3299-0588 FAX: +86-10-3299-0560

http://global.epson.com/products/semicon

TAIWAN

Internal PLL or digital clock input

Software initiated power save mode

EPSON TAIWAN TECHNOLOGY & TRADING LTD.

14F. No. 7. Song Ren Road. Taipei 110 TAIWAN Phone: +886-2-8786-6688

16-bit generic asynchronous CPU interface

Single port camera interface (YUV 4:2:2)

YUV display/capture (YUV 4:2:2, 4:2:0)

YUV to RGB and RGB to YUV converters

COREVDD 1.8 volts and IOVDD 3.0 volts

S1D13717F00A - QFP21 176-pin package

S1D13717B00B - PFBGA12 180-pin package

Support for external MPEG codec interface

Hardware JPEG encoder (YUV 4:2:2, 4:1:1, 4:2:0) Hardware JPEG decoder (YUV 4:4:4, 4:2:2, 4:1:1,

Memory image JPEG encode (YUV 4:2:2, 4:1:1,

View and capture hardware resizer with trimming

Direct and indirect addressing

and reduction functions

FAX: +886-2-8786-6660

SINGAPORE EPSON SINGAPORE PTE., LTD.

1 HarbourFront Place, #03-02 HarbourFront Tower One, SINGAPORE 098633 Phone: +65-6586-5500 FAX: +65-6271-3182

KOREA SEIKO EPSON CORP.

19F, KLI 63 Bldg., 60 Yoido-dong, Youngdeungpo-Ku, Seoul 150-763, KOREA Phone: +82-2-784-6027 FAX: +82-2-767-3677



Document code: X57A-C-001-02.1

NOTICE

No part of this material may be reproduced or duplicated in any form or by any means without the written permission of Seiko Epson. Seiko Epson reserves the right to make changes to this material without notice. Seiko Epson does not assume any liability of any kind arising out of any inaccuracies contained in this material or due to its application or use in any product or circuit and, further, there is no representation that this material is applicable to products requiring high level reliability, such as, medical products. Moreover, no license to any intellectual property rights is granted by implication or otherwise, and there is no representation or warranty that anything made in accordance with this material will be free from any patent or copyright infringement of a third party. When exporting the products or technology described in this material, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You are requested not to use, to resell, to export and/or to otherwise dispose of the products (and any technical information furnished, if any) for the development and/or manufacture of weapon of mass destruction or for other military purposes.

All brands or product names mentioned herein are trademarks and/or registered trademarks of their respective companies. ©Seiko Epson Corporation 2004, 2017. All rights reserved.