



	2 3 4	_
	PRODUCT NO.WITH PICK-UP CAPPACKAGING10105989-001LFNOTRAY10105989-001CLFYESTAPE & REEL	
A		A
_	10.0 10.0 10.0 15.875 15.00 15.875 15.00 15.875 15.00 15.	
В	$\begin{array}{c c c c c c c c c c c c c c c c c c c $	В
, FC	WITH PICK-UP CAP ATTACHMENT $0.60\pm0.05$ $1.27(5X)$ $0.60\pm0.05$ $0.65\pm0.05(20X)$ $0.60\pm0.05$ $0.10$ $0.10$ $0.10$ $31.75$ $3.00$	с
right FCI.	SCALE 2.000 RECOMMENDED PCB LAYOUT I. MATERIAL:	
C opyr	HOUSING & PICK-UP CAP: HIGH TEMPERATURE THERMOPLASTIC, BLACK, UL94V-0 CONTACT & HOLD DOWN: COPPER ALLOY 2. FINISH: CONTACT: 1.27um MIN. Ni UNDERPLATE OVERALL, 1.91um MIN. 100% MATTE Sn(LEAD-FREE) ON SOLDERTAIL, 0.38um MIN. Au ON CONTACT AREA HOLD DOWN: 1.91um MIN. 100% MATTE Sn(LEAD-FREE) OVER 1.27um MIN. Ni UNDERPLATE OVERALL 4. THIS PRODUCT SPEC.: GS-12-282 4. THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008 5. THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECONDS IN A CONVECTION, INFRA-RED OR VAPOR PHASE REFLOW OVEN CONTACT & SAS PLUG	D
	ZBL6. A SYMBOL ZBL WILL BE NEXT TO ANY DIMENSION, VIEW OR NOTE WHICH HAS BEEN Image: Customer and the current drawing revision Im	]