


RECOMMENDED P.C.B. LAYOUT



CIRCUIT

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT RATINGS: 25mA @24VDC.
5. MATERIAL (TERMINALS/CONTACTS):
PHOSPHOR BRONZE w/Gold Plate over
Nickel Plate
6. INSULATION RESISTANCE:
100Mega-ohms min @500VDC
7. CONTACT RESISTANCE (INITIAL):
50mILLI-ohms @2-4VDC @100mA
8. OPERATING FORCE: 1000gf max.
9. TRAVEL: 2mm typical
10. PACKAGED: DISPENSING TUBES
WITH ALL POLES IN THE "OFF" POSITION.
11. ▲ DESIGNATE MAJOR:
SOLDERING RECOMMENDATION:
KEEP ALL SWITCHES IN OFF POSITION DURING
SOLDERING AND CLEANING PROCESS.
12. ▲ SOLDERING RECOMMENDATION:

E-SWITCH®

TITLE		KAP1104V (RECESSED TOP SIDE DN)	
REV.	ECN No.	DATE	CHKD
A	12023	4/1/02	CJB
DESCRIPTION		DATE	CHKD
RELEASED FOR PRODUCTION		4/1/02	CJB
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED			
SCALE	DATE	DR	DWG
2:1	4/01/02	CJB	N411244
TITLE			REV
KAP1104V (RECESSED TOP SIDE DN)			A