

173-61200

Article Number: 173-61200



Description: Electromagnetic Protection Braided Sleeving, Flame Retardant, 12 mm Dia, PET;TNCU, TCBK, 164ft/Reel

Base Data	Local Order Number	173-61200
	Type	HEGEMIPV012
	Color	Tin-coloured and Black (TCBK)
	Features and Benefits	<ul style="list-style-type: none"> • The patented material mix of the HEGMIPV0 braided sleeving offer electromagnetic protection and secure cable bundling. • The special combination of tin-plated copper and PBTV0 yarn offers optimal inside and outside abrasion resistance. • In restricted space areas, HEGMIPV0 is easy to apply without any threads and breaks in the metal.
	Quantity Per	metre
	Product Description	HellermannTyton's patented Helagaine HEGEMIP braided sleeving offers electromagnetic protection on highly sensitive electronic applications. This material mix of braided sleeving is self-extinguishing, according to UL94 V0, and is particularly suitable for areas where fire protection is imperative.
	Short Description	Electromagnetic Protection Braided Sleeving, Flame Retardant, 12 mm Dia, PET;TNCU, TCBK, 164ft/Reel
	Product Dimensions	Length L (Imperial)
Length L (Metric)		50.0m
Reel Length (imperial)		164.0ft
Bundle Diameter Min. (Imperial)		0.39"
Bundle Diameter Min. (Metric)		10mm
Bundle Diameter Max. (Imperial)		0.59"
Bundle Diameter Max. (Metric)		15mm
Diameter D (imperial)		0.47"
Diameter D (metric)		12mm
Nominal Diameter (Imperial)		1/2"
Nominal Diameter (Metric)		12mm

173-61200

Material and Specifications		
	Material	Tin-plated copper (TNCU)
	Material Shortcut	TNCU
	Flammability	FMVSS 302
	Halogenfree	No
	Operating Temperature	-40°F to +302°F (-40°C to +150°C)
	REACH Compliant (Article 33)	Yes
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	164ft
	Package Quantity (Metric)	50m
	Customs Number(Schedule B)	5902100000
	Content Unit (BMEcat)	metre
	Weight (imperial)	10.58
	Weight (Metric)	48.0g/M