

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



EVO connector set, B24 series, plastic housing, consisting of sleeve housing, panel mounting base, push-in contact inserts: 1407735, 1407736, 1407660, 1407656, 1407671

Product Features

- Lower costs than metal version
- Labeling option using 9 x 20 mm marking label
- Low weight
- Lower risk of condensation
- Both contact insert PE sheets are connected by means of a metal frame integrated in the sleeve housing
- Metal inlays ensure leading PE contact with angled plugs
- Completely corrosion-resistant
- Halogen-free plastic
- Impact test according to IK 08
- Marking label can be attached



Key Commercial Data

Packing unit	1 pc
Weight per Piece (excluding packing)	640.0 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

General

Number of positions	24+PE
Туре	B24
Connection method	Push-in connection
Cable exit	straight



Technical data

General

IP66
IP66 (with closed protective cover)
4 (UL50e / NEMA 250)
4X (UL50e / NEMA 250)
12 (UL50e / NEMA 250)
Push-in connection
500 V
6 kV
16 A

Standards and Regulations

Flammability rating according to UL 94 V0	lammability rating according to UL 94	I VO
---	---------------------------------------	------

Articles in set

Contact insert - HC-B 24-I-PT-F - 1407735



HEAVYCON socket insert, B24 series, 24 + PE-pos., push-in connection

Contact insert - HC-B 24-I-PT-M - 1407736



HEAVYCON pin insert, B24 series, 24 + PE-pos., push-in connection

Housing - HC-EVO-B24-BWSC-PLRBK - 1407660



HEAVYCON EVO panel mounting base, plastic housing, B24, with single locking latch, height 30.5 mm, with flat gasket, with protective cover

03/14/2016 Page 2 / 5



Articles in set

Housing - HC-EVO-B24-HHFS-PLBK - 1407656



HEAVYCON EVO sleeve housing, plastic, with bayonet flange for EVO screw connection, B24, for single locking latch, height: 87.5 mm, without EVO screw connection

Cable gland - HC-B-G-M32-PLRBK - 1407671



EVO plastic cable gland with bayonet locking, for housing series B, size M32, cable diameter: 11 ... 21 mm

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440202

ETIM

ETIM 3.0	EC000438
ETIM 4.0	EC000437
ETIM 5.0	EC000437

UNSPSC

UNSPSC 6.01	30211923
UNSPSC 7.0901	39121522
UNSPSC 11	39121522
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522



Approvals	
Approvals	
Approvals	
EAC / EAC	
Ex Approvals	
Approvals submitted	
Approval details	
EAC	
EAC	

Drawings

Schematic diagram

13 🖷	• 1
14 🛛	• 2
15 🖷	• 3
16 🛛	• 4
17 🛛	• 5
18 🛛	• 6
19 🖷	• 7
20 🛛	• 8
21 🜒	• 9
22 🜒	• 10
23 🜒	• 11
24 🜒	• 12

Pin assignment, connection side, pin


Schematic diagram

3
4
5
6
7
8
9
20
21
22
23
24


Pin assignment, connection side, socket

03/14/2016 Page 4 / 5






Dimensional drawing



Derating diagram

Dimensional drawing

Dimensional drawing



Panel cutout

Phoenix Contact 2016 $\ensuremath{\mathbb{C}}$ - all rights reserved http://www.phoenixcontact.com