

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 20

BY TE CONNECTIVITY

ALL RIGHTS RESERVED.

REVISIONS

変更

P	LTR	DESCRIPTION	DATE	DWN	APVD
	C	REVISED	28APR2014	T.S	N.Y

0.7
0.33

1.3
1.08 REF

2.3
1.67 REF

-2:本図
-2:AS SHOWN

AA - AA
SCALE 20:1

AB - AB
SCALE 20:1

1.8
0.8
5.9
AA
AB
AB
AA

1 材料:黄銅

2 仕上げ:全面ニッケル下地めっき
接触部及び圧着部に0.2μm以上の金めっき

3 AWG#26, AWG#28対応

対応電線: UL1571 AWG#26	対応電線: UL1571 AWG#28
素線数/素線径: 7/0.16mm ²	素線数/素線径: 7/0.127mm ²
絶縁被覆径: ϕ 0.94- ϕ 1.20	絶縁被覆径: ϕ 0.84- ϕ 0.92

1 MATERIAL: BRASS

2 FINISH: Ni UNDER PLATING ALL SURFACE
CONTACT AND CRIMP AREA: Au PLATING 0.2μm MIN.

3 WIRE SIZE AWG#26, AWG#28

APPLICABLE WIRES: UL1571 AWG#26	APPLICABLE WIRES: UL1571 AWG#28
NUMBER OF CONDUCTORS/ DIAMETER OF A CONDUCTOR: 7/0.16mm ²	NUMBER OF CONDUCTORS/ DIAMETER OF A CONDUCTOR: 7/0.127mm ²
INSULATION DIAMETER: ϕ 0.94- ϕ 1.20	INSULATION DIAMETER: ϕ 0.84- ϕ 0.92

WIRE RANGE
抱合電線断面積 3

INSULATION DIA
被覆外径 4

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 18MAY2010

H. URUSHIBATA

CHK 18MAY2010

N. YAMASAKI

APVD 18MAY2010

T. MASUDA

PRODUCT SPEC

108-78658

APPLICATION SPEC

114-5446

WEIGHT -

NAME
名称 POST CONTACT
1.5VP REMODEL

SIZE	CAGE CODE	DRAWING NO 番号	RESTRICTED TO
A3	-	C-2069391	-

DIMENSIONS:
単位: 概
mmTOLERANCES UNLESS
OTHERWISE SPECIFIED:

一般公差 ±0.2
0 PLC ±
1 PLC ±0.5
2 PLC ±0.13
3 PLC ±0.013
4 PLC ±0.000J
ANGLES ±1

MATERIAL
材料

1

FINISH
仕上

2

Customer Drawing SCALE 10:1 SHEET 1 OF 1 REV C

1470-19 (3/13)