

126-00041

# HellermannTyton

Article Number: 126-00041

Description: Arrowhead Push Mount Cable Tie, 4.5" Long, 18lb, Panel Thickness .19"-.22", PA66, Natural, 100/pkg



Base Data	
Local Order Number	126-00041
Type	T18RWPM
Color	Natural (NA)
Features and Benefits	<ul style="list-style-type: none"> <li>• Easy and quick insertion ideal for production environment.</li> <li>• Tie "clicks" into place upon final installation signaling installer insertion is complete.</li> <li>• Arrowhead style mount provides low insertion and high extraction force.</li> </ul>
Quantity Per	bag
Product Description	Arrowhead Wing Push Ties design helps stabilize the tie in high vibration applications. This can be used on sheet metal, wood, and cast iron.
Short Description	Arrowhead Push Mount Cable Tie, 4.5" Long, 18lb, Panel Thickness .19"-.22", PA66, Natural, 100/pkg
Product Dimensions	
Minimum Tensile Strength (Imperial)	18.0lbs
Minimum Tensile Strength (Metric)	80N
Length L (Imperial)	4.5"
Length L (Metric)	113.0mm
Fixation Method	Arrowhead
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Inside Serrated
Width W (Imperial)	0.1"
Width W (Metric)	2.5mm
Width W2 (Imperial)	0.25"
Width W2 (Metric)	6.4mm
Height H (Imperial)	0.23"
Height H (Metric)	5.8mm

126-00041



Product Dimensions	Bundle Diameter Min. (Imperial)	0.06"
	Bundle Diameter Min. (Metric)	1.5mm
	Bundle Diameter Max. (Imperial)	0.87"
	Bundle Diameter Max. (Metric)	22.2mm
	Disc Diameter (Imperial)	0.5"
	Disc Diameter (Metric)	13.1mm
	Panel Thickness Max. (Imperial)	0.13"
	Panel Thickness Max. (Metric)	3.2mm
	Panel Thickness Min. (Imperial)	0.06"
	Panel Thickness Min. (Metric)	1.52mm
	Mounting Hole Diameter D (Imperial)	0.19 - 0.22"
	Mounting Hole Diameter D (Metric)	4.8 - 5.6 mm
	Mounting Hole Diameter D Min. (Imperial)	0.19"
	Mounting Hole Diameter D Max. (Imperial)	0.22"
	Thickness T (Imperial)	0.043"
Thickness T (Metric)	1.1mm	
Material and Specifications		
	Material	Polyamide 6.6 (PA66)
	Material Shortcut	PA66
	Flammability	UL 94 V2
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	UL
Logistic and Packaging		
	Package Quantity (Imperial)	100
	Package Quantity (Metric)	100
	Customs Number(Schedule B)	3926909987