



Article Number: 110-09112

Description: Mark 9 Pneumatic - Top Air Supply Connection, includes

tool and quick connect fittings.

performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T50-T250), clamp and button head ties. Like the MK7P, HellermannTyton's MKSP incorporates the next level of ergonomic improvement with its low weight, comfortable grip and easy trigger depression. Very durable, the pneumatic MKSP features adjustable, easy to read tension settings. Lock-out features are available. The MKPP is available with lower air attachment (standard) or can be ordered with an upper air attachment. Quantity Per Product Description The Mark 9 Pneumatic (MKSP) is constructed with heavy duty parts to ensure that in performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T50-T250), clamp and button head ties. Technical Description Includes Mark 9 Pneumatic tool and quick connect fittings with upper air coption for top air connection. Includes a hanger for an optional overhead tool balancer (not included). Ergonomic tool uses pneumatic power and accomplishes rapid tension and cuyt-off with one trigger depression. Short Description Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings. Air Attachment upper air connection Air Supply onol lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5" Power Supply Dry or lubricated air	Base Data		
Type MK9P Features and benefits The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T60-T250), clamp and button head ties. Like the MK7P, HellermannTyton's MK9P incorporates the next level of ergonomic improvement with its low weight, comfortable grip and easy trigger depression. Very durable, the pneumatic MK9P teatures adjustable, easy to read tension settings. Lock-out features are available. The MK9P is available with lower air attachment (standard) or can be ordered with an upper air attachment. Quantity Per carton Product Description The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T50-T250), clamp and button head ties. Technical Description Includes Mark 9 Pneumatic tool and quick connect fittings with upper air coption for top air connection. Includes a hange for an optional overhead tool balancer (not included). Ergonomic tool uses pneumatic power and accomplishes rapid tension and cuty-off with one trigger depression. Short Description Air Attachment upper air connection Air Supply Air Attachment upper air connection Air Supply non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5* Power Supply Dry or lubricated air		Land Order Newborn	AMZADIJA
Features and benefits The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that i performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T50-T250), clamp and button head ties. Like the MK7P, HellermannTyton's MK9P incorporates the next level of ergonomic improvement with its low weight, comfortable grip and easy trigger depression. Very durable, the pneumatic MK9P leatures adjustable, easy to read tension settings. Lock-out features are available with lower air attachment (standard) or can be ordered with an upper air attachment. Quantity Per Carton Product Description The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that i performs optimally in demanding environments. It is ideally designed to apply heavy duty test (T50-T250), clamp and button head ties. Technical Description Includes Mark 9 Pneumatic tool and quick connect fittings with upper air coption for top air connection. Includes a hange for an optional overhead tool belancer (not included). Ergonomic tool uses pneuamatic power and accomplishes rapid tension and cuyl-off with one trigger depression. Short Description Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings. Product Dimensions Air Attachment upper air connection Air Supply non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5° Power Supply Dry or lubricated air		Local Order Number	MK9PUA
performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T50-T250), clamp and button head ties. Like the MK7P, HellermannTyton's MKOP incorporates the next level of ergonomic improvement with its low weight, comfortable grip and easy trigger depression. Very durable, the pneumatic MKSP features adjustable, easy to read tension settings. Lock-out features are available. The MKSP is available with lower air attachment (standard) or can be ordered with an upper air attachment. Quantity Per Product Description The Mark 9 Pneumatic (MKSP) is constructed with heavy duty parts to ensure that it performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T50-T250), clamp and button head ties. Technical Description Includes Mark 9 Pneumatic tool and quick connect fittings with upper air coption for top air connection. Includes a hanger for an optional overhead tool balancer (not included). Ergonomic tool uses pneumatic power and accomplishes rapid tension and cuyt-off with one trigger depression. Short Description Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings. Product Dimensions Air Attachment upper air connection Air Supply on lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5* Power Supply Dry or lubricated air		Туре	MK9P
improvement with its low weight, comfortable grip and easy trigger depression. Very durable, the pneumatic MK9P features adjustable, easy to read tension settings. Lock-out features are available. The MK9P is available with lower air attachment (standard) or can be ordered with an upper air attachment. Quantity Per Carton Product Description The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T50-T250), clamp and button head ties. Includes Mark 9 Pneumatic tool and quick connect fittings with upper air coption for top air connection. Includes a hanger for an optional overhead tool balancer (not included). Ergonomic tool uses pneumanatic power and accomplishes rapid tension and cuty-toff with one trigger depression. Short Description Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings. Air Attachment upper air connection Air Supply non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5* Power Supply Dry or lubricated air		Features and benefits	The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in demanding environments. It is ideally designed to apply heavy-duty ties (T50-T250), clamp and button head ties.
an upper air attachment. Quantity Per Carton Product Description The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that i performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (150-1250), clamp and button head lies. Technical Description Includes Mark 9 Pneumatic tool and quick connect fittings with upper air coption for top air connection. Includes a hanger for an optional overhead tool balancer (not included). Ergonomic tool uses pneuamatic power and accomplishes rapid tension and cuyt-off with one trigger depression. Short Description Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings. Product Dimensions Air Attachment upper air connection Air Supply non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) Dry or lubricated air			improvement with its low weight, comfortable grip and easy trigger depression. Very durable, the pneumatic MK9P features adjustable, easy to read tension settings.
Product Description The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that i performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T50-T250), clamp and button head ties. Technical Description Includes Mark 9 Pneumatic tool and quick connect fittings with upper air coption for top air connection. Includes a hanger for an optional overhead tool balancer (not included). Ergonomic tool uses pneuamatic power and accomplishes rapid tension and cuty-off with one trigger depression. Short Description Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings. Product Dimensions Air Attachment upper air connection non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) Dry or lubricated air			· · · ·
performs optimally in demanding environments. It is ideally designed to apply heavy duty ties (T50-T250), clamp and button head ties. Technical Description Includes Mark 9 Pneumatic tool and quick connect fittings with upper air coption for top air connection. Includes a hanger for an optional overhead tool balancer (not included). Ergonomic tool uses pneumatic power and accomplishes rapid tension and cuty-off with one trigger depression. Short Description Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings. Product Dimensions Air Attachment upper air connection Air Supply non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5" Power Supply Dry or lubricated air		Quantity Per	carton
top air connection. Includes a hanger for an optional overhead tool balancer (not included). Ergonomic tool uses pneumatic power and accomplishes rapid tension and cuyt-off with one trigger depression. Short Description Mark 9 Pneumatic - Top Air Supply Connection, includes tool and quick connect fittings. Product Dimensions Air Attachment upper air connection Air Supply non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5" Power Supply Dry or lubricated air		Product Description	The Mark 9 Pneumatic (MK9P) is constructed with heavy duty parts to ensure that it performs optimally in demanding environments. It is ideally designed to apply heavy-duty ties (T50-T250), clamp and button head ties.
Product Dimensions Air Attachment upper air connection Air Supply non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5" Power Supply Dry or lubricated air		Technical Description	included). Ergonomic tool uses pneuamatic power and accomplishes rapid tension
Dimensions Air Attachment upper air connection Air Supply non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5" Power Supply Dry or lubricated air		Short Description	1 11 1
Air Supply non lubricated / lubricated Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) Dry or lubricated air			
Cycle Time 2 strokes per second Number of cycles 1000000 Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5" Power Supply Dry or lubricated air		Air Attachment	upper air connection
Number of cycles Air Pressure PSI 90 Tension Setting Tools Cable Tie Width Max. (Imperial) Power Supply Adjustable Dry or lubricated air		Air Supply	non lubricated / lubricated
Air Pressure PSI 90 Tension Setting Tools Adjustable Cable Tie Width Max. (Imperial) 0.5" Power Supply Dry or lubricated air		Cycle Time	2 strokes per second
Tension Setting Tools Cable Tie Width Max. (Imperial) Power Supply Adjustable 0.5" Dry or lubricated air		Number of cycles	1000000
Cable Tie Width Max. (Imperial) Power Supply Dry or lubricated air		Air Pressure PSI	90
Power Supply Dry or lubricated air		Tension Setting Tools	Adjustable
		Cable Tie Width Max. (Imperial)	0.5"
Toncion Force		Power Supply	Dry or lubricated air
rension roice Adjustable		Tension Force	Adjustable

generated on: 5/2/2017

110-09112



Material and Specifications		
	ROHS Compliant	Yes
Logistic and Packaging		
	Package Quantity (Imperial)	1
	Package Quantity (Metric)	1
	Customs Number(Schedule B)	8467920090
	Weight (imperial)	32oz
	Weight (Metric)	0.91kg

generated on: 5/2/2017