

S8VK-G Power Supply

Tough, Easy, Compact



Features & Benefits

- Increased temperature range provides stable operation
- Compact size provide less heat build-up in the panel allowing longer life for the S8VK-G and surrounding components
- Power Boost increases S8VK-G life when used with inductive load applications
- Can withstand 5G of shock and vibration allowing it to be used in extreme applications such as stone crushing machines

Specifications

- Increased Temperature Ratings: -40°C to 70°C (-40°F to 158°F)
- 15 W, 30 W, 60 W conform to UL Class 2 Output
- Power Boost function at 120%
- 5 Year Warranty

Ordering Information

Power Rating	Input Voltage	Output Voltage	Output Current	Boost Current	Model
15 W	Single Phase 100 to 240 VAC 90 to 350 VDC	5 V	3 A	3.6 A	S8VK-G01505
		12 V	1.2 A	1.44 A	S8VK-G01512
		24 V	0.65 A	0.76 A	S8VK-G01524
30 W		5 V	5 A	6 A	S8VK-G03005
		12 V	2.5 A	3 A	S8VK-G03012
		24 V	1.3 A	1.56 A	S8VK-G03024
60 W		12 V	4.5 A	5.4 A	S8VK-G06012
		24 V	2.5 A	3 A	S8VK-G06024
120 W		24 V	5 A	6 A	S8VK-G12024
240 W		24 V	10 A	12 A	S8VK-G24024
		48 V	5 A	6 A	S8VK-G24048
480 W		24 V	20 A	24 A	S8VK-G48024
	48 V	10 A	12 A	S8VK-G48048	