


# Housing - HC-ADV-B06-SHFH-2STM25-EEE - 1408656

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://download.phoenixcontact.com)







## Key commercial data

Packing unit	11
Weight per Piece (excluding packing)	400.0 GRM
Custom tariff number	85389099
Country of origin	China

#### Technical data

#### **Dimensions**

Height	68 mm
Width	57 mm
Length	92 mm

#### Ambient conditions

Degree of protection for housing	IP65
	IP68 (0.2 bar/24 h)
	IP69K
Ambient temperature (operation)	-40 °C 125 °C

#### General

Note	For contact inserts HC-B06, BB10, DD24, M
Design	B6
Housing type	Box mounting bases
Locking type	Screw locking
Fixing screws	M6
No. of cable exits	2



# Housing - HC-ADV-B06-SHFH-2STM25-EEE - 1408656

## Technical data

## General

Cable exit	Lateral
Screw connection	None
Type of the screw connection	2x M25
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	Uncoated
Connection	To ensure optimum shielding, any insulating powder coating must be removed from the housing support area on the control cabinet panel

### Classifications

### eCl@ss

eCl@ss 4.0	27140816
eCl@ss 4.1	27140816
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

#### **ETIM**

ETIM 4.0	EC000437
ETIM 5.0	EC000437

### **UNSPSC**

UNSPSC 6.01	31261502
UNSPSC 7.0901	31261502
UNSPSC 11	31261502
UNSPSC 12.01	31261502
UNSPSC 13.2	31261502

### Accessories

Accessories

Protective cover



# Housing - HC-ADV-B06-SHFH-2STM25-EEE - 1408656

#### Accessories

Protective covers - HC-B 6-TMS-SD-IP65 - 1690778



HEAVYCON ADVANCE IP65 protective cover B6, for panel mounting side, with screw locking, with retaining cord, diameter of retaining cord eyelet 3 mm


Protective covers - HC-B 6-TMS-SD-IP50 - 1690736



HEAVYCON ADVANCE IP50 protective cover B6, for panel mounting side, with clip locking, with retaining cord, diameter of retaining cord eyelet 3 mm

### **Drawings**

#### Dimensioned drawing



Dimensional drawing

© Phoenix Contact 2013 - all rights reserved http://www.phoenixcontact.com