

111-01915



Article Number: 111-01915

Description: Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66UV, Black, 1000/pkg

Base Data	Local Order Number	T18R0UVM4
	Type	T18R
	Color	Black (BK)
	Features and Benefits	<ul style="list-style-type: none"> • UV stabilized cable ties contain an inhibitor which prolongs the life of the tie in UV exposures . • Inside serrations allow for strong hold on cables and wire bundles. • Head design provides high tensile strength with very low insertion force. • Bent tail ensures a quick and simple installation.
	Quantity Per	bag
	Product Description	HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.
	Short Description	Standard Cable Tie, 4" Long, 18lb Tensile Strength, PA66UV, Black, 1000/pkg
	Product Dimensions	Minimum Tensile Strength (Imperial)
Minimum Tensile Strength (Metric)		80.0N
Length L (Imperial)		4.0"
Length L (Metric)		100.0mm
Fixation Method		None
Identification Plate Position		none
Releasable Closure		No
Tie Closure		plastic pawl
Variant		Inside Serrated
Width W (Imperial)		0.1"
Width W (Metric)		2.45mm
Bundle Diameter Min. (Imperial)		0.06"
Bundle Diameter Min. (Metric)		1.5mm

111-01915



Product Dimensions	Bundle Diameter Max. (Imperial)	0.86"
	Bundle Diameter Max. (Metric)	22.0mm
	Thickness T (Metric)	1.0mm
Material and Specifications	Material	Polyamide 6.6 UV-resistant (PA66UV)
	Material Shortcut	PA66UV
	US MILSPEC	MS3367-4-0
	Flammability	UL 94 V2
	Halogenfree	Yes
	Operating Temperature	-40°F to +185°F (-40°C to +85°C)
	ROHS Compliant	Yes
	Certification/Specification	SAE - AS33671
Logistic and Packaging	Package Quantity (Imperial)	1000
	Package Quantity (Metric)	1000
	Customs Number(Schedule B)	3926909987