



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: P100-000-R

### AT Serial Adapter (DB9F to DB25M)

#### Highlights

- Converts DB9 male serial connector to a DB25 male serial connector
- Fully shielded against EMI/RFI interference
- Gold Plated Connectors



#### Description

Tripp Lite's serial adapter has gold plated connectors and will convert a DB9 male connector into a DB25 male connector. Lets a serial device with a DB9 connector attach to a PC with a DB25 port. PVC premold encapsulates individual conductors to ensure electrical isolation and relieve stress. 28 AWG stranded tinned copper conductors are individually insulated in polypropylene. This minimizes cross talk and ensures high-speed, error-free transmission. Clamshell retail packaging.

#### System Requirements

- DB25F serial port on a PC or cable

#### Package Includes

- Serial Adapter Block DB9F to DB25M Gold Connectors

#### Features

- Connects a DB9 serial device to a DB25 cable or port
- Gold plated contacts and connectors for superior conductivity

#### Specifications

<b>UPC Codes</b>	
Unit Carton UPC#	037332011626
<b>CONNECTIONS</b>	
Connector A	 DB9 (FEMALE)
Connector B	 DB25 (MALE)
<b>WARRANTY</b>	

**Product Warranty Period  
(Worldwide)**

Lifetime limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">P100-000-R</a>	AT Serial Adapter (DB9F to DB25M)	1
<a href="#">P404-006</a>	6-ft. AT Serial Modem Gold Cable (DB25M to DB9F)	1
<a href="#">P454-006</a>	6-ft. Null Modem Gold Cable (DB9 F/M)	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=2200](http://www.tripplite.com/en/products/model.cfm?txtModelID=2200).

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.