

855-14215

Article Number: 855-14215



Description: Connector, Fiber Optic SC Multimode OM1 (62.5/125), Pre-Polished (Cleave & Insert)

| | | |
|------------------------|-----------------------------|--|
| Base Data | Local Order Number | PFCSC |
| | Type | PFCSC |
| | Color | Beige (BGE) |
| | Features and benefits | <ul style="list-style-type: none"> • Factory-polished zirconia ceramic ferrules for quick and reliable field installations. • Unique wedge clip retains connector shape for precision connection. • Easy to use- no epoxy, heat curing, polishing or special tools required. • Color coded for easy identification. • Meet ANSI/TIA/EIA 568-C standards. • Meet ANSI/TIA/EIA 604 (FOCIS) connector interface requirements. |
| | Quantity Per | bag |
| | Product Description | Pre-polished connectors provide high performance and eliminate the need for the time consuming task of hand polishing ferrules in the field. A factory pre-cleaved fiber stub and index-matching gel combine to offer an immediate low loss termination of single mode or multimode fiber. |
| | Technical Description | Pre-Polished SC 62.5/125 Multimode Fiber Connector, Beige |
| | Short Description | Connector, Fiber Optic SC Multimode OM1 (62.5/125), Pre-Polished (Cleave & Insert) |
| | Product Dimensions | Port count |
| Width W (Metric) | | 28mm |
| Height H (Metric) | | 9.3mm |
| | | |
| Logistic and Packaging | Package Quantity (Imperial) | 1 |
| | Package Quantity (Metric) | 1 |
| | Customs Number(Schedule B) | 8536700000 |
| | | |

855-14215

HellermannTyton
