



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: 602

Waber-by-Tripp Lite 5-outlet Power Strip with 6-ft. Cord



Highlights

- 5 outlets
- 6-ft. cord
- 8.6-in. overall length
- No switch

Description

The Waber-by-Tripp Lite 602 Power Strip offers a convenient method of power distribution in workbench, wallmount or floor mount applications. Includes 5 NEMA 5-15R output receptacles with 1.188-inch center-to-center spacing, 6-foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cable clutter and enables the connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes the 602 ideal for distributing alternate waveform UPS or generator power. Features rugged all-metal housing, 15-amp resettable circuit breaker and attractive blue/gray color scheme.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 5 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

Applications

- Offers multiple outlet power distribution in workbench, wallmount or floor mount applications. Unfiltered electrical pass-through makes the 602 ideal for distributing alternate waveform UPS or generator power to protected equipment.

Package Includes

- 602 Power Strip
- Warranty information
- Instruction manual

Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 5 NEMA 5-15R output receptacles with 1.188-inch center-to-center outlet spacing
- Keyhole mounting tabs support permanent installation on a wide variety of surfaces
- UL1363 (USA), cUL (Canada)
- 15-amp power handling capacity with circuit breaker
- 6-foot AC line cord

Specifications

| OUTPUT | |
|---|---|
| Frequency compatibility | 50 / 60 Hz |
| Circuit Breaker (amps) | 15 |
| Outlet quantity / type | 5 NEMA 5-15R |
| Outlet spacing | 1.188 in. |
| Outlet orientation | Single row of 5 |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 15A 120V |
| Input connection type | NEMA 5-15P |
| Input cord length (ft.) | 6 |
| Input cord length (m) | 1.8288 |
| Voltage compatibility (VAC) | 120 |
| LEDS ALARMS & SWITCHES | |
| Switches | No switch |
| PHYSICAL | |
| Unit Dimensions (HWD/in) | 7.38 x 2.5 x 1.5 |
| Unit Dimensions (HWD/cm) | 18.7 x 6.35 x 3.8 |
| Material of construction | Metal |
| Integrated keyhole mounting tabs | Keyhole mounting tabs enable mounting to a variety of surfaces |
| Receptacle Color | Black |
| AC line cord color | Black |
| Outlets center to center measurement | 30mm |
| Keyhole slot center to center measurement | Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45 |
| CERTIFICATIONS | |
| UL1363 (Power Tap) | UL1363 |
| cUL / CSA (Canada) | cUL |
| WARRANTY | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?variables.txtModelID=1954.

Copyright © 2013 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.